

TRMS 300A_{AC} CURRENT CLAMP METER

DCM100MINI



- TRMS
- Display with 6000 counts and backlight
- Current up to 300A ac
- Inrush current
- Non Contact Voltage detection
- High Frequency Rejection
- 10mA resolution
- 1.5% basic ACA accuracy
- Auto ranging
- Auto Power Off
- Safety rating: CATIII 600V



DCM100MINI

TRMS 300A_{AC} CURRENT CLAMP METER

General	
Display	6000 counts
Sampling rate	2 times/sec
Auto power off	✓
Backlight	✓
Hold	✓
Auto-ranging	✓
High Frequency Rejection mode (HFR)	✓
Low Battery Indication	✓
Jaw opening size	24mm
Dimensions	60x147x31mm
Weight	140g
Batteries	LR44 or A76 x 2 pcs button cell
Standars	EC 61010-1, IEC/EN61010-2-032
Safety rating	CAT III 600V
Accesories included	Button Cells, Manual, Carrying pouch

DCM100MINI

TRMS 300A_{AC} CURRENT CLAMP METER

Specs		
FUNCTION	RANGE	RESOLUTION
TRMS		✓
AC Current	60.00A/300.0A AC	0.01A/0.1A
Inrush current	300.0A	0.1A
HFR	60.00A/300.0A AC	0.01A/0.1A
VoltSense (NCV)		80V ~ 600V

Product Code Information	
SKU	KPSDCM100MINICBINT
EAN code	8435394787251
UPC code	810053677742
Pcs/export carton	36