

LEAKAGE CLAMP METER

KPS-PF10



- ☐ Current leakage clamp with Ø31 mm jaw
- ☐ 2000 counts
- ☐ Three manually selected scales:
2mA / 20mA / 60A
- ☐ Retention of readings
- ☐ Auto power off
- ☐ Low battery indication
- ☐ CAT. III 600V according to EN 61010



KPS-PF10

LEAKAGE CLAMP METER

General	
Power Supply	2 × 1.5V AAA Batteries
Product Size	176 mm × 59 mm × 28 mm
Product Weight	150g
Certificate	CE, UKCA, RoHS
Safety Rating	CAT III 600V

Specs	
Display Counts	2000
Jaw Opening	Φ31mm/1.2"
Auto Power Off	✓
Data Hold	✓
Low Battery Display	✓

Function	Range	Resolution	Accuracy
AC Current	2 mA	0.001 mA	± (2.0% + 10 digits)
	20 mA	0.01 mA	± (2.0% + 8 digits)
	60A (<50A)	0.1A	± (2.0% + 5 digits)
	60A (>50A)	0.1A	± (3.0% + 5 digits)

KPS-PF10

LEAKAGE CLAMP METER

Product Code Information

SKU	KPSPA440CBINT
EAN code	8435394747231
UPC code	810053670217
Pcs/export carton	20

EMEA

✉ info.emea@kps-intl.com

C/ Picu Castiellu, Parcelas i1-i4, Argame,
Morcin 33163, Asturias, Spain

CANADA & USA

✉ info.na@kps-intl.com

6509 Northpark Blvd Unit 400,
Charlotte, NC 28216 USA

UNITED KINGDOM

✉ info.uk@kps-intl.com

Warwick House Queen Street 65-66,
London, England, EC4R 1EB UK